

Document type

Technical Data Sheet

Name	DUNE SUEDE
Description	Decorative paint for interior vertical architectural finishes. Dune Suede is a highly versatile interior wall finish with a matt look and soft touch. The smoothness of the finish can be enhanced even further with the application of a topcoat of Soft Touch protective treatment. The possibilities for application of Dune Suede are vast. One approach results in a sober and elegant finish with subtle variations in colour intensity, making it an ideal choice for large surfaces and even entire homes. Another method involves creating textured 3D effects through finishes with reliefs, offering a unique and eye-catching alternative. These textured finishes can also be further accentuated with the addition of our metallic waxes.
Composition	Glass microspheres and carbonates immersed in a water-based acrylic polymer-based binder
Appearance	Thick liquid
Colour	White, it can be tinted in any colour with STUCCO ITALIANO COLOUR SYSTEM
Packaging	14 L net polyethylene containers
Application	By hand, using a trowel. To be applied in one or two coats.
Type of Surface	Interior walls
Dilution	Ready to use
Consumption	750 gr/ sqm after 2 coats
Drying	4 hours at 20°C / 68°F to the touch 24 hours at 20°C / 68°F below the surface
Application temperatures	min 8 max 35°C – R.U. < 85% ca
Coat Thickness	Less than 2 mm
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Specific Weight	1.3 ± 0.1 (kg/l)
pH	8.4 ± 0.2
Flammability	European Class of Reaction to Fire A1: non-combustible, no contribution to fire
Shelf life	24 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° - 35°C in a dry, dark environment
Safety Norms	This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.

Application Instructions

WARNINGS

We recommend using materials from the same production batch for the same project. If you must use different batches, we suggest mixing their material together to avoid any slight variations in shading.

To ensure proper usage, dilution, and application of the products mentioned in these pages, please consult the corresponding technical data sheets.

During application and for the following 24 hours, protect the surfaces from sudden temperature change, direct sun light and water. Don't apply in temperatures below 8°C or above 35°. During application make sure that the work area isn't too damp to avoid problems with application times.

APPLICATION

Wall Preparation

Make sure the walls are perfectly smooth or smooth them out. Apply a coat of PRIMER 4 or DEKO PRIMER. Walls with old paint: Remove all old, unstable paint and apply a coat of UNIVERSAL PRIMER diluted 1 to 8-9 with water. Smooth it out with fine stucco to obtain a smooth, uniform surface. Apply a coat of DEKO PRIMER or PRIMER 4. Allow it to dry completely.

Colouring

It is necessary to check the compatibility of the colorants before use, if they are different from those supplied by STUCCO ITALIANO. After adding the colourant to the product, stir slowly for 1,5-2 minutes.

Application

Apply with the metallic trowel in two coats on a well prepared background primed with DEKO PRIMER. Leave the first coat to dry completely and give a light sanding with P320 paper before applying the second coat. The second coat must be applied homogeneously to obtain a harmonious design made of soft light-dark effect. Once completely dry, you can sand all the surface once again with very soft hand. Remove the dust and apply Soft Touch protection in two layers with a short hair roller, taking care to roll the second layer when the first is completely dry.

Other Application Techniques

This material is ideal for 3D finishes. In fact, it can be applied in thicknesses from 1 to 6 mm and maintains an excellent thixotropy during application. In any case, it must be protected, once well dry, with Soft Touch varnish or with a layer of our UNIVERSAL PRIMER diluted 1 to 10 with water.

Dune Suede is the ideal plaster for decoration with stencils.

Wash the tools with water

Finish Protection (optional)

The finish can be protected with SOFT TOUCH, a water-based polyurethane varnish in one component with a soft touch

Maintenance

No special work is required in maintenance, just remove the dust.

Tools

SI TROWEL. Clean tools with water after use.



We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.