

Document type	Technical Data Sheet
Name	SPRITZCOLOR
Description	Decorative paint for interior vertical architectural finishes. SPRITZCOLOUR is a washable finish with white speckles that can be tinted in any colour, yielding from antique to modern effects. Ideal for high-traffic spaces due to strength and dirt resistance. Easy application results in quick, high decorative impact.
Composition	Small flakes immersed in a water-based acrylic polymer-based binder
Appearance	Thick liquid
Colour	White dots on a transparent base. The dots can be tinted in any colour with STUCCO ITALIANO COLOUR SYSTEM
Packaging	2.5 L net polyethylene containers
Application	By hand, using a spalter, brush or spray. To be applied in one or two coats.
Type of Surface	Interior walls
Dilution	Ready to use
Consumption	130 gr/ sqm after 2 coats
Drying	4 hours at 20°C / 68°F to the touch 24 hours at 20°C / 68°F below the surface
Application temperatures	min 8 max 35°C – R.U. < 85% ca
Coat Thickness	Less than 1 mm
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Specific Weight	1.09 ± 0.05 (kg/l)
Flammability	European Class of Reaction to Fire A1: non-combustible, no contribution to fire
Shelf life	24 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° - 35°C in a dry, dark environment
Safety Norms	This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
Application Instructions	<p>WARNINGS</p> <p>We recommend using materials from the same production batch for the same project. If you must use different batches, we suggest mixing their material together to avoid any slight variations in shading.</p> <p>To ensure proper usage, dilution, and application of the products mentioned in these pages, please consult the corresponding technical data sheets.</p>

During application and for the following 24 hours, protect the surfaces from sudden temperature change, direct sun light and water. Don't apply in temperatures below 8°C or above 35°. During application make sure that the work area isn't too damp to avoid problems with application times.

APPLICATION

Wall Preparation

Ensure that the walls are smooth. If necessary, apply enough material and plaster to achieve a smooth finish. If the walls have old paint, remove any unstable paint. Dilute UNIVERSAL PRIMER with water at a ratio of 1 to 8, and apply it to the walls. After 4 hours, apply DEKO PRIMER using a brush or roller. Be careful not to leave any marks on the surface. Wait for the primer to dry completely.

When using SPRITZCOLOR decorative paint, choose the colour of DEKO PRIMER carefully. The colour of the final finish will depend on the background colour of the DEKO PRIMER, and the white dots in SPRITZCOLOR will stand out against this background. To achieve the desired result, make sure to tint DEKO PRIMER in the final desired colour. For example, if you want a blue finish with white flakes, tint DEKO PRIMER in blue.

Colouring

The background colour on which the white flakes will stand out is defined by the colour of the DEKO PRIMER coat below it. Therefore, if you want to keep the flakes white, do not tint SPRITZCOLOR. Any tint added to SPRITZCOLOR will be absorbed by the flakes

Brush application

Apply by brush or spalter. Immerse the brush directly into the material and apply it to one place on the wall and from there, use short (8-14 cm) brushstrokes, moving it in all directions. Continue repeating the same operation until the wall ends, taking care to cover the entire surface, but leaving more material in some areas and less in others. After 5 or 6 hours (at 20°C), you can repeat the operation and, after applying the product, wait for about 60 minutes. Then, with a dry brush, go over the entire surface moving in all directions with long movements of about 18-20 cm, compressing the particles slightly.

Application by trowel

Apply with a small, metal trowel using 20-30 cm strokes, crisscrossing in all directions. After 5 or 6 hours, repeat the operation and after about 60 minutes, when the drying is about to begin, compress the surface with a metal or a light, plastic spatula making strokes in all directions, while compressing the small particles. Wash the tools with water.

Spray application

This product has been thought to be applied by spray. After having painted the wall with coloured DEKO PRIMER, Apply the product in one or two coats depending on the desired effect, using a low pressure machine.

Maintenance

No special work is required in maintenance, just remove the dust.

Tools

SPALTER, BRUSH, TERRE TROWEL. Clean tools with water after use.



We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.