

| Document type | Technical Data Sheet |
|--------------------------|---|
| Name | MIRROR+ |
| Description | Decorative paint for interior vertical architectural finishes. MIRROR+ is an acrylic solution for glossy and washable Venetian plaster finishes. Since it can also be tinted and thinned for easy brush or sponge application, it is ideal for marbling techniques. The finish remains polishable for a few days after application. |
| Composition | Marble powders and acrylic resins |
| Appearance | Cream |
| Colour | White, it can be tinted in any colour with STUCCO ITALIANO COLOUR SYSTEM |
| Packaging | 7 kg net polyethylene containers |
| Application | By hand, using a trowel. To be applied in two coats. |
| Type of Surface | Interior walls |
| Dilution | Ready to use, it can be diluted for the drawing of marble veins with brushes |
| Consumption | 720 g / sqm |
| Drying | 4 hours at 20°C / 68°F to the touch 24 hours at 20°C / 68°F below the surface |
| Application temperatures | min 8 max 35°C – R.U. < 85% ca |
| Coat Thickness | Less than 2 mm |
| VOC Classification | EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/I (2010). This product contains less than 200 g/I of VOC. |
| Specific Weight | 1.83 ± 0.05 (kg/l) |
| Flammability | European Class of Reaction to Fire A1: non-combustible, no contribution to fire |
| Shelf life | 24 months when stored according to the recommended guidelines |
| Storage | In original sealed packaging between 5° - 35°C in a dry, dark environment |
| Safety Norms | This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet. |
| Disposal | Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging. |
| Application Instructions | WARNINGS We recommend using materials from the same production batch for the same project. If you must use different batches, we suggest mixing their material together to avoid any slight variations in shading. To ensure proper usage, dilution, and application of the products mentioned in these pages, please consult the corresponding technical data sheets. |

TDS MIRROR+

May 23

1 of 2

Stucco Italiano Srl Via Rovereto, 20 - 36030 Costabissara (VI), Italy | Tel +39 0444 700991 | info@stuccoitaliano.it C.F / VAT IT 03744780242 | SDI: M5UXCR1



| | During application and for the following 24 hours, protect the surfaces from sudden temperature change, direct sun light and water. Don't apply in temperatures below 8°C or above 35°. During application make sure that the work area isn't too damp to avoid problems with application times. |
|---------------------------------|--|
| | APPLICATION |
| | Wall Preparation |
| | Treat a perfectly smooth surface with one coat of either PRIMER 4 or DEKO PRIMER. DEKO PRIMER requires a slightly thicker first coat of MIRROR+ than necessary with PRIMER 4. |
| | Colouring |
| | The product can be tinted in any colour with STUCCO ITALIANO COLOUR SYSTEM. It is necessary to check the compatibility of the colorants before use, if they are different from those supplied by STUCCO ITALIANO. After adding the colourant to the product, stir slowly for 1,5-2 minutes. |
| | Application by trowel |
| | Apply the first coat of coloured MIRROR+ trying not to leave ridges but making a thin and uniform layer over the entire wall. |
| | Once dry, any raised imperfections are removed using a spatula or by sanding, and with a clean surface, apply the second coat of MIRROR+. Before it is completely dry, a third coat can be applied by applying a very thin layer and polishing when almost completely dry. A characteristic of this product is that the polishing process can be done even on completely dry material and up to 24 hours after it dried. |
| | After the second coat, the surface can be painted with a marble effect using the diluted and coloured product applied with a brush, sponge, tampon, or even with the dense material applied with a spatula or trowel. Trowel polishing will be done during drying to remove any ridges and when the product is completely dry. |
| Finish Protection (optional) | N/A |
| Maintenance | No special work is required in maintenance, just remove the dust. |
| Tools | SI TROWEL. Clean tools with water after use. |

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.

May 23

Stucco Italiano Srl Via Rovereto, 20 - 36030 Costabissara (VI), Italy | Tel +39 0444 700991 | info@stuccoitaliano.it C.F / VAT IT 03744780242 | SDI: M5UXCR1