

Document type **Technical Data Sheet**

Name	PRIMER 4
Description	This primer provides good adhesion and low penetration in the substrate. It is a breathable primer that provides adhesion to support and facilitates the application of many decorative paints, such as: KRISTALIUM, LIBERTY EPOQUE, NAPPA, SUPERNOVA, SPRITZCOLOUR, TERRA D'ARTE, OSSIDATO LIGHT. Its prerogative is to be easily tinted to match the colour of the decorative finish, or to provide a coloured base for those decorative finishes that have transparency qualities.
Composition	Special acrylic polymers, very fine marble sand, additives, and water
Appearance	Liquid
Colour	Transparent
Packaging	5 L polyethylene packaging
Application	By hand, using a roller
Type of Surface	Interiors, architectural vertical surfaces.
Dilution	Ready to use, but accepts dilution up to 10% with water
Consumption	100 - 120 ml / sqm
Drying	2 hours at 20°C (60°F) to the touch 24 hours at 20°C (60°F) below the surface
Application temperatures	min 8 max 35°C – R.U. < 85% ca
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Shelf life	24 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° and 35°C in a dry, dark environment
Safety Norms	This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
Application Instructions	<p>WARNINGS</p> <p>To ensure proper usage, dilution, and application of the products mentioned in these pages, please consult the corresponding technical data sheets.</p> <p>During application and for the following 24 hours, protect the surfaces from sudden temperature change, direct sun light and water. Don't apply in temperatures below 8°C or above 35°. During application make sure that the work area isn't too damp to avoid problems with application times.</p>

APPLICATION

The product is ready to use, but can be diluted up to 10% with water.

Characteristic of this primer is to be easily coloured. Many finishes, such as KRISTALIUM, NAPPA, SPRITZCOLOUR and OSSIDATO LIGHT - need a background that is colored in their own or similar tint, or need a coloured background as base colour. Please consult these products' technical data sheet for more information.

To obtain a perfect background we recommend the application spray or with a short hair roller.

Tools

Roller. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.