

Document type	Technical Data Sheet
Name	PRIMER Q
Description	PRIMER Q is a gritty, strong grip primer. It is the perfect solution for high-stress plasters that require a primer with maximum adhesion performance. As a base layer, it creates a secure bond to the substrate for materials such as MAGNESITE TERRAZZO, and REINFORCED MICROCEMENT. It is also effective as a base when applying plasters to wooden surfaces such as tables and other furniture.
Composition	Special acrylic resins, fine quartz sand, adhesion promoter additives, thixotropic agents and water
Appearance	Dense liquid
Colour	Transparent white
Packaging	6 kg polyethylene packaging
Application	By hand, using a roller
Type of Surface	Architectural surfaces, interior and exterior
Dilution	Ready to use, it accepts a 10% dilution with water
Consumption	150 - 180 ml / sqm
Drying	2 hours at 20°C (60°F) to the touch 24 hours at 20°C (60°F) below the surface
Application temperatures	min 8 max 35°C – R.U. < 85% ca
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Shelf life	24 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° and 35°C in a dry, dark environment
Safety Norms	This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
Application Instructions	<p>SURFACE PREPARATION</p> <p>The substrate must be thoroughly dry and clean, devoid of any oils, grease, paint residues, or other removable substances. Prioritize repairing any cracks or fissures present in the substrate. When applying PRIMER Q on non-solid substrates, it is crucial to consolidate them first, by applying a layer of UNIVERSAL PRIMER, diluted according to the provided instruction.</p> <p>APPLICATION</p>

Primer Q can be applied directly or diluted up to 10%. You can use a brush or roller to apply the primer evenly. Typically, one layer of Primer Q is sufficient for regular applications. However, if you require enhanced waterproofing or when using it on wooden furniture before plaster application, a second layer is recommended. Apply the second layer only after the first layer has completely dried, which typically takes around three to four hours under average conditions.

Tools

Roller or brush. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.