

Document type	Technical Data Sheet
Name	SDA – SLOW DRYING ADDITIVE
Description	It is a retardant paste for lime products. It lengthens the drying time allowing applications on surfaces otherwise too large. It can be used on all our products based on lime and cement. It comes in 0,9 kg buckets. The quantity to be added to the material depends on your own needs, the maximum is a full jar per 24 kg bucket of material.
Composition	Resins and hydro-retainer additives
Appearance	White cream
Packaging	900 g polyethylene packaging
Application	Mix with the lime plaster, or other plaster, with the help of an electric mixer
Where to use it	It can be added to all lime or cement-based plasters, gypsum putties, lime paint.
Dilution	Ready to use
Consumption	Adding a 900 g package to 24 kg of lime plaster extends the drying time by approximately 25%. Don't use more than 900 grams of SDA per every 24 kg of plaster.
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/l): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Shelf life	24 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° and 35°C in a dry, dark environment
Safety Norms	This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label.
Disposal	Product must be disposed of according to norms and regulations in force. Follow directions on the packaging.
Application Instructions	<p>APPLICATION</p> <p>SDA can be applied to slow the drying time of all lime and cement-based plasters. When adding it to wet plasters, mix it carefully and let the product set for a minimum of 20 minutes before you start applying on any surface.</p>
Tools	Electric mixer. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.