

Document type	Technical Data Sheet
<b>Name</b>	<b>SOFT TOUCH</b>
<b>Description</b>	SOFT TOUCH is a one-component, water-based polyurethane matt varnish that has a smooth, leather-like touch. It is the ideal final treatment for DUNE SUEDE and DUNE SPATOLATO finishes, but it can also be used on any of our smooth decorative finishes and as a covering for various objects.
<b>Composition</b>	Acryl-polyurethane, water-based one component resin
<b>Appearance</b>	Dense liquid
<b>Colour</b>	Transparent
<b>Packaging</b>	1 L polyethylene packaging
<b>Application</b>	By hand, using a roller or brush
<b>Type of Surface</b>	SOFT TOUCH varnish is a versatile solution for protecting various floor finishes, including PASTELLONE, MAGNESITE TERRAZZO, and REINFORCED MICROCEMENT. It can also be effectively applied to wall finishes in wet areas, such as inside showers finished with MARMORINO MEDIUM and TADELAKT.
<b>Dilution</b>	Ready-to-use. If desired, it can be diluted with distilled water up to 5% of its weight
<b>Consumption</b>	200 ml/sqm after two coats.
<b>Drying</b>	At 20°C and 50% RH: Dust dry: 30 minutes Re-coatable: after 2 hours Loadable: 14 days
<b>Application temperatures</b>	min 15 max 30°C – R.U. < 85% ca
<b>VOC Classification</b>	The maximum VOC content permitted by the EU-Directive 2004/42 (Product category IIA/e) is in the ready-to-use state 130g/l (Limit 2010). The maximum content of this product is < 130 g/l VOC.
<b>Shelf life</b>	24 months when stored according to the recommended guidelines
<b>Storage</b>	In original sealed packaging between 8° and 35°C in a dry, dark environment
<b>Safety Norms</b>	Avoid inhaling mist. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet.
<b>Disposal</b>	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
<b>Application Instructions</b>	<p><b>WARNINGS</b></p> <p>Use only noncorrosive tools and containers (e.g. stainless steel or plastic).</p> <p>The temperature of the varnish and object and the ambient temperature should not be lower than 15°C (danger of blisters forming).</p> <p>Always keep the container closed. Protect the contents from drying (skin formation). Take care when opening the container so that no dried residues fall into the varnish.</p>

Skin flakes or scaling do not dissolve and can only be removed by filtering (e.g. through a nylon gauze).

In order to guarantee flawless durability, sufficient thickness of the total coating must be observed.

To assess the varnish system under practical conditions it is best to create a test surface.

During application and for the following 72 hours, protect the surfaces from sudden temperature change, direct sun light and water.

#### APPLICATION

**Overview:** The product is best applied with a roller, and a minimum of two coats is recommended to achieve paramount results. Shake or stir well before use.

**Application:** 2 or 3 coats using a flat brush or roller. Use a micro-fibre coated sealing roller or a paintbrush for water-based varnishes. Dilute the varnish with 3-5% water if necessary and do not apply too thickly.

**Drying,** at 20 °C and 50% relative humidity: Allow a drying time of approx. 2 hours and sand lightly with 240 grit before applying the second coat. Apply the third coat only after allowing to dry overnight and sanding with 240 grit. Coatings applied too thickly, and high humidity influence the drying. Air circulation (0.5–1.5 m/min.) and a higher temperature reduce the drying time. The treated surface can be carefully walked on after approx. 8 hours. After 14 days full use is possible, and carpets can be laid.

If applying on PASTELLONE, wait for a minimum of 24 hours for the finish to dry completely before applying the product.

When necessary, the varnish can be re-applied, after having washed well and lightly sanded the entire surface to be treated.

#### Tools

Roller or brush. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product.