

Document type	Technical Data Sheet
Name	BEESWAX METALLIC
Description	BEESWAX METALLIC is a semi-transparent decorative and protective treatment specially formulated for enhancing the beauty of decorative plaster finishes like Venetian Plaster. This product is made of natural beeswax, infused with metallic mica powders, and designed to increase the shine and protection against liquids and dirt on smooth finishes, while providing a decorative metallic effect
Composition	Beeswax, mica powders, vegetable oil, soap, water, additives.
Appearance	Milky
Versions	COPPER, GOLD, SILVER
Packaging	2 kg polyethylene packaging
Application	By hand, using a soft cloth or sponge. It is then polished with a non-woven fabric
Where to use it	Interior and exterior mineral-based wall decorative finishes.
Dilution	Ready to use, it accepts dilution with water
Consumption	40-50 g/sqm depending on the texture of the plaster.
Drying	2-3 hours at 20°C
Application temperatures	min 8 max 35°C – R.U. < 85% ca
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Shelf life	36 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° and 35°C in a dry, dark environment
Safety Norms	This product may cause allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
Application Instructions	<p>BEESWAX METALLIC offers a range of benefits for plaster finishes. It increases their protection against liquids and dirt, it enhances their shine, and provides a decorative metallic effect. Apply BEESWAX METALLIC after a minimum of 12 hours from the application of the plaster. If you plan to dilute BEESWAX METALLIC with water, apply it after a minimum of 24 hours from the application of the plaster.</p> <p>To effectively protect your plaster finish, apply BEESWAX METALLIC using a sponge or a soft cloth, making sure to cover each spot twice. After a brief period of about a minute or two, when the wax is almost dry but not completely, gently remove the excess using a soft cloth like our NON-WOVEN FABRIC, and rub to polish. For maximum protection, apply two coats, allowing 12 hours between each application. Remember to remove excess wax after each coat. For a more refined finish, particularly with vibrant colours, you can tint the wax using the same pigments used for the plaster. Apply the coloured wax as usual.</p>

**Tools**

Soft cloth or sponge. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product.