

Document type **Technical Data Sheet**

Name **BEESWAX**

Description Beeswax is a traditional protective treatment for Venetian plaster finishes. It is a natural, ecologic wax made from beeswax. It is used to increase the shine and the protection against liquid and dirt on smooth finishes such as MARMORINO (FINE, MEDIUM, COARSE, METALLIC),TADELAKT and LAVA PLASTER, as wells as more textured finishes such as TRAVERTINO, BETON STUCCO, DOLOMIA and STARS.

Composition Beeswax, vegetable oil, soap, water, additives.

Appearance Milky

Colour Transparent white, it can be coloured to match the tone of the finish on which it is applied

Packaging 1 kg, 2 kg, or 15 kg polyethylene packaging

Application By hand, using a soft cloth or sponge. It is then polished with a non-woven fabric

Where to use it Interior mineral-based wall decorative finishes.

Dilution Ready to use, it accepts dilution with water

Consumption 40-50 g/sqm depending on the texture of the plaster.

Drying 2-3 hours at 20°C

Application temperatures min 8 max 35°C – R.U. < 85% ca

VOC Classification EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.

Shelf life 36 months when stored according to the recommended guidelines

Storage In original sealed packaging between 5° and 35°C in a dry, dark environment

Safety Norms It is important to adhere to the prevailing safety and hygiene standards while using it. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label.

Disposal Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.

Application Instructions BEESWAX offers a range of benefits for plaster finishes, including increased protection against liquids and dirt, enhance its shine, the ability to change the finish's colour and achieve special effects with MARMORINO VELVET, TRAVERTINO, or other finishes. Apply beeswax after a minimum of 12 hours from the application of the plaster. If you plan to dilute BEESWAX with water, apply it after a minimum of 24 hours from the application of the plaster.

- To effectively protect your plaster finish, apply BEESWAX using a sponge or a soft cloth, making sure to cover each spot twice. After a brief period of about a minute or two, when the wax is almost dry but not completely, gently remove the excess using a soft cloth like our NON-WOVEN FABRIC, and rub to polish. For maximum protection, apply two coats, allowing 12 hours between each application. Remember to remove excess wax after each coat. For a more refined finish, particularly with vibrant colours, you can tint the wax using the same pigments used for the plaster. Apply the coloured wax as usual.

- To change the colour of the finish, tint BEESWAX in a different colour than the plaster finish.
- To achieve an antique effect on Velvet Marmorino and Travertino, dilute the tinted wax and apply it onto dry finish using a paintbrush. Remove any excess while the wax is still wet, using a soft cloth or a sponge.

Tools

Soft cloth or sponge. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product.