

Document type	Technical Data Sheet
Name	LIBERTY ARENA
Description	Decorative paint for interior vertical architectural finishes. Liberty Arena is a metallic finish for interior walls that delivers a unique visual experience. The material is comprised of special quartz micro-spheres that create soft, striated reliefs reminiscent of sand, as well as mineral powders that give the surfaces a iridescent, pearlescent effect that changes with the angle of light. The result is a dynamic and captivating finish that adds depth and dimension to any interior space.
Versions	GOLD, SILVER
Composition	Quartz microspheres and mineral powders dispersed in an acrylic binder.
Appearance	Thick liquid
Colour	The GOLD version is a golden yellow and can be tinted further to achieve different shades of gold, bronze, oranges and greens. The SILVER version is white, and can be tinted in any colour with STUCCO ITALIANO COLOUR SYSTEM.
Packaging	5 L net polyethylene containers
Application	By hand, using a spalter or brush, decorative roller, or marine sponge. To be applied in one or two coats.
Type of Surface	Interior walls
Dilution	Ready to use, a dilution with water up to 10% of its weight is possible
Consumption	160-200 gr/ sqm after 2 coats
Drying	4 hours at 20°C / 68°F to the touch 24 hours at 20°C / 68°F below the surface
Application temperatures	min 8 max 35°C – R.U. < 85% ca
Coat Thickness	Less than 1 mm
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Specific Weight	1.44 ± 0.05 (kg/l)
Flammability	European Class of Reaction to Fire A1: non-combustible, no contribution to fire
Shelf life	24 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° - 35°C in a dry, dark environment
Safety Norms	This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
Application Instructions	WARNINGS

We recommend using materials from the same production batch for the same project. If you must use different batches, we suggest mixing their material together to avoid any slight variations in shading.

To ensure proper usage, dilution, and application of the products mentioned in these pages, please consult the corresponding technical data sheets.

During application and for the following 24 hours, protect the surfaces from sudden temperature change, direct sun light and water. Don't apply in temperatures below 8°C or above 35°. During application make sure that the work area isn't too damp to avoid problems with application times.

APPLICATION

Preparing the Wall: prepare the surface by sanding it, removing any dust, and making it smooth. Then, apply a coat of DEKO PRIMER and wait at least 4 hours for it to dry completely.

Application: Using a brush or spalter, apply LIBERTY ARENA unevenly, taking care to avoid creating typical brush lines. When the product is partially dry, use a soft, damp sponge to create irregular areas of accumulation with rotational movements. Apply a second coat if necessary, For more application techniques, please refer to our instructional videos.

Finish Protection (optional)	N/A
Maintenance	No special work is required in maintenance, just remove the dust occasionally.
Tools	SPALTER, BRUSH. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.