

Document type	Technical Data Sheet
Name	LIBERTY EPOQUE
Description	Decorative paint for interior vertical architectural finishes. Liberty Epoque is a washable interior decorative finish that boasts a metallic pearlescent effect, creating an iridescent look that changes with the angle of light reflection, recalling of the soft glow of silk. This breathable coating captures the luxurious essence of the Belle Epoque, with its bright metallic hues.
Versions	GOLD, SILVER
Composition	Mineral powders dispersed in an acrylic binder.
Appearance	Thick liquid
Colour	The GOLD version is a golden yellow and can be tinted further to achieve different shades of gold, bronze, oranges and greens. The SILVER version is white, and can be tinted in any colour with STUCCO ITALIANO COLOUR SYSTEM.
Packaging	5 L net polyethylene containers
Application	By hand, using a spalter or brush, decorative roller, trowel or marine sponge. To be applied in one or two coats.
Type of Surface	Interior walls
Dilution	Ready to use, a dilution with water up to 10% of its weight is possible
Consumption	120-140 gr/ sqm after 2 coats
Drying	4 hours at 20°C / 68°F to the touch 24 hours at 20°C / 68°F below the surface
Application temperatures	min 8 max 35°C – R.U. < 85% ca
Coat Thickness	Less than 1 mm
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Specific Weight	1.27 ± 0.05 (kg/l)
Flammability	European Class of Reaction to Fire A1: non-combustible, no contribution to fire
Shelf life	24 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° - 35°C in a dry, dark environment
Safety Norms	This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
Application Instructions	WARNINGS

We recommend using materials from the same production batch for the same project. If you must use different batches, we suggest mixing their material together to avoid any slight variations in shading.

To ensure proper usage, dilution, and application of the products mentioned in these pages, please consult the corresponding technical data sheets.

During application and for the following 24 hours, protect the surfaces from sudden temperature change, direct sun light and water. Don't apply in temperatures below 8°C or above 35°. During application make sure that the work area isn't too damp to avoid problems with application times.

APPLICATION

Satin Lamé Effect

Prepare the substrate with one coat of UNIVERSAL PRIMER or PRIMER 4.

Leave to dry (approximately 4 hours), and apply the first coat of LIBERTY EPOQUE with a metal trowel, taking care not to leave too many ridges. After 4 hours, apply a second coat of LIBERTY EPOQUE with the metal trowel, in semi-circular movements. Remove the excess ridges by passing the trowel over them.

Brocade Effect

Prepare the substrate with one coat of UNIVERSAL PRIMER or PRIMER 4.

Leave to dry (approximately 4 hours), and apply the first coat of LIBERTY EPOQUE with a metal trowel, taking care not to leave many ridges. After approximately 4 hours, or when dry, apply a second coat of LIBERTY EPOQUE with the metal trowel, in small, circular movement. After 2 or 3 minutes, caress the surface lightly with a SPONGE FLOAT, in small, circular movements. After 3-5 minutes, repeat the same operation with the metal trowel, caressing the surface gently with its blade flat against the wall, in even smaller, circular movements, while removing the excess material.

Finish Protection (optional)	N/A
Maintenance	No special work is required in maintenance, just remove the dust periodically.
Tools	SPALTER, BRUSH, SI TROWEL, SPONGE FOR DECORATIVE EFFECTS. Clean with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.