

Document type	Technical Data Sheet
<b>Name</b>	<b>MINERAL WAX</b>
<b>Description</b>	Our Mineral Wax is a water-based protection for lime and mineral-based finishes. It can be used on both walls and floors, including particularly wet areas like shower boxes. It enhances the surfaces' resistance to liquids and makes cleaning easier.
<b>Composition</b>	Paraffins, water, additives and oil.
<b>Appearance</b>	Amber/transparent, thick cream
<b>Packaging</b>	1 kg or 5 kg polyethylene packaging
<b>Application</b>	By hand, using a trowel or spatula
<b>Where to use it</b>	Lime and mineral-based smooth plaster finishes such as GRASSELLO, MARMORINO FINE, MEDIUM, COARSE and METALLIC; it can be used in combination with ECOTOP on PASTELLONE and ECO TERRAZZO. It can be used on interior and exterior finishes.
<b>Dilution</b>	Ready to use
<b>Consumption</b>	25-30 g/sqm
<b>Drying</b>	2-3 hours at 20°C to the touch, 10 hours in depth
<b>Application temperatures</b>	min 8 max 35°C – R.U. < 85% ca
<b>VOC Classification</b>	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
<b>Shelf life</b>	24 months when stored according to the recommended guidelines
<b>Storage</b>	In original sealed packaging between 5° and 35°C in a dry, dark environment
<b>Safety Norms</b>	It is important to adhere to the prevailing safety and hygiene standards while using it. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label.
<b>Disposal</b>	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
<b>Application Instructions</b>	<p>After the final application of any mineral wall coating, allow at least 72 hours before applying MINERAL WAX. If you've used HYDROCALCE on the wall finish, also wait 72 hours before applying MINERAL WAX.</p> <p>To apply MINERAL WAX effectively, use a spatula or trowel and apply it with a minimum thickness. Allow at least one hour of drying time before proceeding with polishing. Polishing can be done manually using our NON-WOVEN FABRIC or with electrical equipment. For floor applications, a single disk machine can be used for polishing. It's important to avoid leaving excess wax or deposits on the surface. It's crucial to apply all waxes, including MINERAL WAX, in a thin layer as their purpose is to seal the porosity of the underlying material.</p> <p>In the case of absorbing finishes, such as MARMORINO Venetian Plaster, we recommend applying a first layer of BEESWAX followed by a very thin layer of MINERAL WAX. Please note that excessive wax left on the finish may result in stains,</p>

as the greasy components of the wax can be absorbed by the surface. The initial layer of BEESWAX serves to reduce this risk by providing a protective barrier.

Regular maintenance is essential, and we recommend repeating this treatment annually to ensure the coating remains well-maintained. For floor maintenance, small doses of wax can be added regularly to the water used for cleaning. Liquid wax, specifically designed for this purpose, can be requested separately.

**Tools**

Trowel or spatula. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product.