

Document type **Technical Data Sheet**

Name	MARSEILLE SOAP PASTE
Description	It is a traditional natural treatment for Venetian Plaster. It provides a light protection against liquid and dirt to MARMORINO (FINE, MEDIUM and COARSE), MARMORINO METALLIC, BETON STUCCO, TADELAKT and GRASSELLO. Applied with a spatula, it also helps to close small imperfections or pores.
Composition	Pure Marseille soap, water, additives and oil.
Appearance	White, thick paste
Packaging	2 kg L polyethylene packaging
Application	By hand, using a trowel, spatula, sponge or soft cloth
Where to use it	Interior architectural vertical surfaces finished with: BETON STUCCO, GRASSELLO, LAVA PLASTER, MARMORINO FINE, MEDIUM, COARSE AND METALLIC, TADELAKT. It can be used on interior and exterior finishes.
Dilution	The product can be diluted up to 5 times its weight with water, to be applied by brush or sponge.
Consumption	30-60 g/sqm of non-diluted product
Drying	3-5 hours at 20°C
Application temperatures	min 8 max 35°C – R.U. < 85% ca
VOC Classification	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
Shelf life	24 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° and 35°C in a dry, dark environment
Safety Norms	This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
Application Instructions	<p>Apply MARSEILLE SOAP PASTE at least 24 hours after the decorative plaster has been applied. The application can be done using a trowel or, if preferred, by diluting the soap and applying it by hand with a soft cloth or sponge. Carefully wipe off any excess soap with a soft cloth before it fully dries.</p> <p>Note that the soap is white in colour, so when used on very dark finishes it may leave white spots in the pores. Diluting the soap can help mitigate this effect, but the best way to avoid it is to colour the soap to match the finish it is applied upon.</p> <p>Always test on samples or a small area before applying to the entire wall.</p>
Tools	Trowel, spatula, sponge or soft cloth. Clean tools with water after use.



We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product.