

Document type

Technical Data Sheet

Name

PRESEALER - UNIVERSAL

Description

PRESEALER is a transparent, water-based primer formulated with acrylic resins. It is particularly recommended for preparing cement- and lime-based decorative finishes before the application of PU1C or PU2C polyurethane varnish.

The product penetrates and consolidates the surface, equalises substrate absorption and promotes the adhesion and uniform application of subsequent protective coatings. By forming a thin, water-resistant film, it significantly improves the overall water resistance of the complete protective treatment.

Composition

Special acrylic polymers, additives, and water

Appearance

Dense liquid

Colour

Transparent white

Packaging

1 L polyethylene bottle
5 L polyethylene bucket

Application

By hand, using a roller, spray or brush

Type of Surface

Cement or lime-based surface finish

Dilution

Ready to use, no dilution is needed

Consumption

100 ml/sqm. Yield is about 10 sqm per litre of product.

Drying

4 hours at 20°C (60°F) to the touch
24 hours at 20°C (60°F) below the surface

Application temperatures

min 8 max 28°C – R.U. < 85% ca

Shelf life

24 months when stored according to the recommended guidelines

Storage

In original sealed packaging between 5° and 35°C in a dry, dark environment

Safety Norms

This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet.

Disposal

Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.

Application Instructions

WARNINGS

To ensure proper usage, dilution, and application of the products mentioned in these pages, please consult the corresponding technical data sheets. During application and for the following 24 hours, protect the surfaces from sudden temperature change, direct sun light and water. Do not apply on damp flooring or those subject to rising humidity. Don't apply in temperatures below 8°C or above 28°. Equip operators as required by current safety regulations. Adequately ventilate closed areas during the use of the product.

APPLICATION

The PASTELLONE or other plaster finish to be treated must be perfectly dry, and clean from dust and grease. PRESEALER is ready to use and does not need dilution. It can be applied using a sprayer, a roller, or a soft fibre brush. Apply PRESEALER in a single coat, ensuring that the product is evenly distributed over the entire surface to be treated. To obtain an excellent water resistance, apply two coats of product. Avoid excesses or superficial stagnation of the product. Wait at least 4 hours to allow the product to dry completely before applying subsequent coats or other finishes. Always perform preliminary tests on the surface to be treated to avoid possible unwanted effects. Do not apply on flooring that is not perfectly dry or in the presence of rising damp.

Tools

Roller or brush. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.