

**Document type**                      **Technical Data Sheet**

<b>Name</b>	<b>QUARTZ PRIMER</b>
<b>Description</b>	QUARTZ PRIMER is a medium-grit, acrylic-based undercoat for decorative finishes. It is the complementary product of all STUCCO ITALIANO's lime and / or cement-based plasters, <u>excluding</u> MARMORINO FINE, MARMORINO METALLIC and GRASSELLO which require a finer-grained primer, such as our DEKO PRIMER.
<b>Composition</b>	Special acrylic polymers, very fine quartz sand, additives, and water
<b>Appearance</b>	Liquid
<b>Colour</b>	Transparent white
<b>Packaging</b>	5 L polyethylene packaging 15 L polyethylene packaging
<b>Application</b>	By hand, using a roller
<b>Type of Surface</b>	Architectural vertical surfaces, interior and exterior
<b>Dilution</b>	Ready to use, but can be diluted up to 10% with water. When diluting, mix often to avoid sedimentation of the quartz sand.
<b>Consumption</b>	160 - 170 ml / sqm (non-diluted product)
<b>Drying</b>	2 hours at 20°C (60°F) to the touch 24 hours at 20°C (60°F) below the surface
<b>Application temperatures</b>	min 8 max 35°C – R.U. < 85% ca
<b>VOC Classification</b>	EU Directive 2004/42/CE: EU limit value for this product (cat A/I): 200 g/l (2010). This product contains less than 200 g/l of VOC.
<b>Shelf life</b>	24 months when stored according to the recommended guidelines
<b>Storage</b>	In original sealed packaging between 5° and 35°C in a dry, dark environment
<b>Safety Norms</b>	This product may cause skin allergic reactions. It is important to adhere to the prevailing safety and hygiene standards while using it. Refrain from disposing of the product in drains, water bodies, or on the ground. Always keep the product out of reach of children. In the event of ingestion, or allergic reaction seek medical assistance without delay and present the container or label. For further details, consult the safety data sheet.
<b>Disposal</b>	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
<b>Application Instructions</b>	<p><b>WARNINGS</b></p> <p>To ensure proper usage, dilution, and application of the products mentioned in these pages, please consult the corresponding technical data sheets.</p> <p>During application and for the following 24 hours, protect the surfaces from sudden temperature change, direct sun light and water. Don't apply in temperatures below 8°C or above 35°. During application make sure that the work area isn't too damp to avoid problems with application times.</p>



#### APPLICATION

The product is ready to use but can be diluted up to 10% with water.

This product can be applied with a brush or roller in one coat. For applications on wood, for a good sealing, it is advisable to apply two coats of the product.

#### Tools

Roller. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.