

Document type

Technical Data Sheet

Name	Base for Furniture
Description	Base for furniture is a fibrous and flexible undercoat plaster, used as a first coat when applying a decorative plaster on a table, piece of furniture or any other wooden object. Its purpose is to provide a flexible layer capable of accommodating the natural expansion and contraction of wood bodies, and thus to prevent cracks in the decorative plaster finish. It is normally applied after a layer of Primer Q.
Composition	Hydrated lime, Portland cement, marbles powders, fibres, binders.
Appearance	Powder
Colour	White
Packaging	8 kg polyethylene tubs
Application	By hand, using a trowel or spatula
Type of Surface	Wood, plywood, water-resistant or waterproofed MDF
Dilution	422 g of water for every kg of product in powder
Consumption	1.3 – 1.5 kg per square metre.
Drying	4 hours at 20°C / 68°F to the touch 48 hours at 20°C / 68°F below the surface
Application temperatures	min 8 max 35°C – R.U. < 85% ca
Shelf life	18 months when stored according to the recommended guidelines
Storage	In original sealed packaging between 5° and 35°C in a dry, dark environment
Safety Norms	Irritating. / Risk of serious damage to eyes. / Irritating to the skin. / Keep out of children. / Avoid contact with eyes. / In case of contact with eyes, clean immediately with water without rubbing them, and consult a doctor. / Wear suitable gloves and eyes / face protection. / In case of ingestion of the products, consult immediately a doctor showing him the can or the label of the product. Danger labelling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments. The product must be transported, used and stored according to current standards of hygiene and safety.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. Follow directions on the packaging.
Application Instructions	<p>WARNINGS</p> <p>To ensure proper usage, dilution, and application of the products mentioned in these pages, please consult the corresponding technical data sheets.</p> <p>During application and for the following 24 hours, protect the surfaces from sudden temperature change, direct sun light and water. Don't apply in temperatures below 8°C or above 35°. During application make sure that the work area isn't too damp to avoid problems with application times.</p> <p>APPLICATION</p> <p>Apply one coat of diluted BASE FOR FURNITURE using a metal trowel over wooden surfaces previously prepared with PRIMER Q and, if needed, reinforced with fibreglass</p>

mesh.

Once fully dry, the surface is ready for the application of the decorative plaster.

When properly applied to achieve a uniform and smooth finish, **BASE FOR FURNITURE** can serve as a substitute for the first coat of decorative plaster in those finishes that require a three-coat application cycle.

Tools

Trowel / Spatula. Clean tools with water after use.

We have drawn up the material presented above to the best of our technical and experiential knowledge. Nevertheless, our suggestions and recommendations are not guaranteed. All responsibility for the obtained results lies solely with the method and conditions adopted for the application of the product. Such indications constitute valid support for verifying the product's suitability for the specific case. We reserve the right to make modifications to the present information without previous warning.